## IN THE CLAIMS

This is a complete and current listing of the claims, marked with status identifiers in parentheses. The following listing of claims will replace all prior versions and listings of claims in the application.

1.	(Currently Amended) A modular service device (1),
	rising:
	-havinga retaining devicemeans(4)
	for a bearing device, means (5) which can be coupleabled
	thereto;
	-having -a housing (2) having including a
	plurality of predetermined module locations (6a-6d);
	having
	7d) which can each be arranged at the module locations
	(6a-6d)—and—are—_each provided with a connection means
	device for connecting a line which can be connected
	thereto;
	<del>having a</del> coding means_ <del> (9a-9d) per module location</del>
	(6a-6d)—and an opposing coding means—(10a-10d) per
	connection module (7a-7d), for the purpose of providing
	module location-specific assignment;
	havinga latching means <del>(11) at</del> at least
	one of the module locations, $\frac{(6a-6d)}{}$ and ${}$ and ${}$ opposing
	latching means (12)—on at least one of the connection

New PCT National Phase Application Docket No. 32860-000906/US

modules, (7a-7d) for the purpose of respectively providing module location-specific locking and unlocking; and

- 2. (Currently Amended) The modular service—device as claimed in claim 1, <u>further comprising at least one of having—an electrical</u>, electromagnetic <u>ander</u> electronic device unit—(3).
- 3. (Currently Amended) The modular service—device as claimed in claim 1, havingwherein the retaining device includes at least one spring-loaded and self-ringing latching element—(20) as part of the retaining means (4).
- 4. (Currently Amended) The modular service—device as claimed in claim 1, wherein having a multi-pole design of at least one of the connection

modules (7a-7d)-is of a multi-pole design.

- 5. (Currently Amended) The modular service device as claimed in claim 1,\_
- <u>in whichwherein</u> <u>each respective</u> the <u>respective</u> connection <u>device includes at least one of means is in the form of a screw terminal, a spring-loaded terminal <u>or and an insulation displacement contact.</u></u>
- 6. (Currently Amended) The modular service device as claimed in claim 1, wherein
- in which the coding means (9a-9d) is in the formincludes, individually per module location—(6a-6d), of—a recess formed by housing sections, and the opposing coding means (10a-10d) is in the form of includes a bracket element.
- 7. (Currently Amended) The modular <del>service</del> device as claimed in claim 1,\_
- in which wherein the latching means (11) is in the form of includes an elastic lock having a barb, and the opposing latching means (12) is in the form of includes a latch accommodating the barb.
- 8. (Currently Amended) The modular service—device as claimed in claim 1,

New PCT National Phase Application Docket No. 32860-000906/US

in which wherein the contact means (16a, 16b) is in the form of includes at least one of a contact lug or and a contact pin, and the opposing contact means (18) is in the form of includes a fork-shaped contact element.

9. (Currently Amended) The modular service—device as claimed in claim 1—and/or-8,

## having an, further comprising:

- 10. (Currently Amended) The modular service—device as claimed in claim 9,\_
- in which wherein the insulating means (19) is in the form of includes an insulating bracket, in particular of a plug-in element which can be integrated in the housing (2).
- 11. (New) The modular device as claimed in claim 9, wherein the insulating means includes a plug-in element integrated in the housing.
- 12. (New) The modular device as claimed in claim 8, further comprising:

insulating means, arranged at least one of on an end and on a longitudinal side of the contact means, for covering the contact means.

- 13. (New) The modular device as claimed in claim 12, wherein the insulating means includes an insulating bracket.
- 14. (New) The modular device as claimed in claim 12, wherein the insulating means includes a plug-in element integrated in the housing.
- 15. (New) A modular device, comprising:
  - a retaining device for a bearing device, coupleable thereto;
  - a housing including a plurality of predetermined
    module locations;

connection modules, arrangeable at the module locations and each provided with a connection device for connecting a line thereto;

at least one coding and opposing coding device;

at least one latch, at at least one of the module locations and at least one opposing latch on at least one of the connection modules, to respectively provide module location-specific locking and unlocking; and

at least one contact; and

New PCT National Phase Application Docket No. 32860-000906/US

at least one opposing contact adapted to make transversely make contact with respect to a longitudinal side of the at least one contact.

- 16. (New) The modular device as claimed in claim 15, further comprising at least one of an electrical, electromagnetic and electronic device unit.
- 17. (New) The modular device as claimed in claim 15, wherein the retaining device includes at least one spring-loaded and self-ringing latching element.
- 18. (New) The modular device as claimed in claim 15, wherein at least one of the connection modules is of a multipole design.
- 19. (New) The modular device as claimed in claim 15, wherein each respective connection device includes at least one of a screw terminal, a spring-loaded terminal and an insulation displacement contact.
- 20. (New) The modular device as claimed in claim 15, wherein the coding device includes, individually per module location, a recess formed by housing sections, and the opposing coding device includes a bracket element.